SPRAY ADHESIVE · CODE 78

Taftspray 78

Multi-Purpose Spray Adhesive

REF	ISSUED	REVIEWED	PAGE
Product ID: DYQWJ/SPI92	Jan 2022	June 2026	1

PRODUCT DESCRIPTION

TaftSpray 78 is a multipurpose sprayable synthetic elastomer adhesive that bonds to most lightweight materials when dry. It has high tack, good spray coverage, fast drying and low misting. It can stick to paper, felt, cork, wood, plastics, and most lightweight materials.

TYPICAL PROPERTIES

- A high tack, high coverage fast drying, transparent adhesive for permanently bonding foils, carpeting and many lightweight foams, paper, cardboard, felt and cloth to painted or unpainted metals, wood, hardboards and other base materials.
- It provides high initial “grab” with sufficient open time to allow for positioning of materials.
- Low soak-in gives better appearance and higher adhesive coverage.
- Soft, non-dimpling glue lines.

PHYSICAL PROPERTIES

Solid Content (by wt)	25%
Base	Synthetic Elastomers
Colour (wet & dry)	Translucent
Net Weight (approximately)	450 grams
Spray Pattern	Low mist, fine particles spray
Flash Point	-40°C
Coverage *10 gram/m2, m2/Kg	23
% Volatile Organic Content (VOC)	52%
Hazardous Air Pollutants	None

APPLICATION/HANDLING INFORMATION

Directions for Use

DIRECTIONS FOR USE

- 1. Surface Preparation: Surfaces must be clean, dry and free from dirt, dust, oil, loose paint, wax or grease, etc.
- 2. Application Temperature: For best results the temperature of the adhesive and the surfaces being bonded should be at least 18℃.
- 3. Application:
- Shake can well.
- Turn spray tip so arrow points to dot on rim. (Note: Always point spray tip away from yourself and others.)
- Hold can 15-20 cm from surface to be sprayed.
- Make bond while adhesive is aggressively tacky.
- After use, invert can, depress spray tip until spray is free of adhesive.
- Clean spray tip with turpentine*
- 4. Bonding Range:
- 1 surface – 10 seconds to 15 minutes
- 2 surface – 10 seconds to 30 minutes
- Extra strong bonds – Spray both surfaces and allow a minimum of 30 seconds drying time.

STORAGE

Store product at 16°C – 28°C for maximum storage life. Do not expose product to direct sunlight or direct flame. High temperature may reduce storage life. Lower temperature may increase the viscosity of a temporary nature.

SHELF LIFE

This product has a maximum shelf life of 24 months from date of manufacturing.

PRECAUTIONARY INFORMATION

Refer to Safety Data Sheet for health and safety information when handling this product.

COMPLIANCE AND QUALITY

RoHS statements and Safety Data Sheets for this product are available on request. Contact the MightyLoc team and we will send the current documents.

Vitrochem Technology Pte Ltd

1, Bukit Batok Crescent, #05-40 WCEGA Plaza, Singapore 658064 · +65 6766 7191 · +65 6766 7187 · www.mightyloc.com

Data last reviewed **June 2026**.

All recommendations for the use of our products are based on the current state of our knowledge. The Buyer remains responsible for satisfying itself that the product is suitable for its intended process or purpose. Since we cannot control the application, use, or processing of the product, we accept no responsibility on that basis. Refer to the current controlled data sheet, or contact us, before production use.